

## EC Certificate of Conformity

**0913 - CPD - 2012 / 07**

In compliance with Council Directive 89/106/EEC of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products (the Construction Products Directive or CPD), as later amended, it has been stated that the construction product

**Microprismatic Retro-reflective Sheeting  
ORALITE® 5910 High Intensity Prismatic Grade, Native Colours  
for fixed, vertical road traffic signs,  
(modalities attached),**

**placed on the market by:**

**ORAFOL Europe GmbH  
Orafolstrasse 2  
D-16515 Oranienburg  
Germany**

**and produced in the factory:**

**Werk Oranienburg  
Orafolstrasse 2  
D-16515 Oranienburg  
Germany**

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the approval body (AB) - Technický a skúšobný ústav stavebný (TSUS) - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and that the notified body No. 0913 - Prüf-, Überwachungs- und Zertifizierungsgemeinschaft der Straßenausstatter (StrAus-Zert) - performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in the ETA

**ETA 12/0478, valid from 2013-06-27 to 2018-01-21**

were applied and that the product fulfils all the prescribed requirements. For detailed information in relation to the performance characteristics of the product, the ETA itself, mentioned above, should be consulted.

This certificate was first issued on **February 5<sup>th</sup> 2013** and remains valid until the date of expiry of the ETA as long as the conditions laid down in the ETA in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Hagen, 28 June 2013



Christian Barga  
Dipl.-Ing.  
Leiter StrAus-Zert

**Attachment to EC Certificate of Conformity 0913 - CPD - 2012 / 07 (6 pages)**

The above certified microprismatic retroreflective sheeting ORALITE® 5910 High Intensity Prismatic Grade to be used for fixed, vertical road traffic signs is admitted for the following original dyed colours:

**Original dyed retroreflective sheeting:**

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 2	Coefficient of retroreflection ETA 12/0478 tab. 3	Impact resistance ETA 12/0478 tab. 5	Resistance to weathering ETA 12/0478 tab. 6 und 7
White	ORALITE® 5910-010 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass
Yellow	ORALITE® 5910-020 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5910-030 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5910-050 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5910-060 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass
Brown	ORALITE® 5910-080 High Intensity Prismatic Grade	pass, B2	R2 Europe	pass	pass

The above certified microprismatic retroreflective sheeting ORALITE® 5910 High Intensity Prismatic Grade to be used for fixed, vertical road traffic signs is accepted to be coloured by the below listed materials:

**Lettering Film:**

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5081-070 Lettering Film	NR1	-	pass	pass

**Screenprinting Colours:**

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 8	Coefficient of retroreflection ETA 12/0478 tab. 9	Impact resistance ETA 12/0478 tab. 11	Resistance to weathering ETA 12/0478 tab. 12 und 13
on white sheeting	ORALITE® 5910-010 High Intensity Prismatic Grade and				
Yellow	ORALITE® 5018-020 Screen Printing Ink	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5018-030 Screen Printing Ink	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5018-050 Screen Printing Ink	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5018-060 Screen Printing Ink	pass, B2	R2 Europe	pass	pass
Orange	ORALITE® 5018-035 Screen Printing Ink	pass, B2	R2 Europe	pass	pass

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5018-070 Screenprinting Ink	NR1	-	pass	pass

**Coloured Laminates:**

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 14	Coefficient of retroreflection ETA 12/0478 tab. 15	Impact resistance ETA 12/0478 tab. 17	Resistance to weathering ETA 12/0478 tab. 18 und 19
on white sheeting	ORALITE® 5910-010 High Intensity Prismatic Grade and				
Transpa- rent	ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass
Yellow	ORALITE® 5061-020 Transparent Film	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5061-030 Transparent Film	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5061-050 Transparent Film	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5061-060 Transparent Film	pass, B2	R2 Europe	pass	pass
Orange	ORALITE® 5061-035 Transparent Film	pass, B2	R2 Europe	pass	pass
Brown	ORALITE® 5061-080 Transparent Film	pass, B2	R2 Europe	pass	pass

### Digital Printing Colours:

The digital printing is processed on white retroreflective sheeting with the digital printing systems ORALITE® UV Digital Traffic Sign Printer or AGFA ANAPURNA M2050 High-Speed-UV-Inkjet-System and is to be laminated with the transparent laminate ORALITE® 5061-000 Transparent Film.

Colour on white sheeting	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 32	Coefficient of retroreflection ETA 12/0478 tab. 33	Impact resistance ETA 12/0478 tab. 35	Resistance to weathering ETA 12/0478 tab. 36 und 37
Yellow	ORALITE® 5019-020 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5019-030 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5019-050 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5019-060 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass
Brown	ORALITE® 5019-080 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	pass, B2	R2 Europe	pass	pass

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5019-070 UV Digital Printing Ink and ORALITE® 5061-000 Transparent Film	NR1	-	pass	pass

If the colour Black is printed solely, this material combination is admitted to be used without the transparent laminate.

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5019-070 UV Digital Printing Ink	NR1	-	pass	pass

**Clear protective overlay film:**

Clear protective overlay films (Anti-Dew and Anti-Graffiti) are always admitted in combination with retroreflective sheeting and a colouring process.

**Anti-Dew:**

The original dyed retroreflective sheeting is accepted to be laminated with the clear protective overlay film ORALITE® 5090 Anti-Dew Film for the following colours.

Original dyed retroreflective-sheeting ORALITE® 5910 High Intensity Prismatic Grade

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 20	Coefficient of retroreflection ETA 12/0478 tab. 21	Impact resistance ETA 12/0478 tab. 23	Resistance to weathering ETA 12/0478 tab. 24 und 25
White	ORALITE® 5910-010 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Yellow	ORALITE® 5910-020 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5910-030 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5910-050 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5910-060 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Brown	ORALITE® 5910-080 High Intensity Prismatic Grade and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass

The original dyed white retroreflective sheeting is accepted to be laminated with the coloured transparent laminate ORALITE® 5061 Transparent Film and the clear protective overlay film ORALITE® 5090 Anti-Dew Film for the following colours.

Original dyed retroreflective-sheeting ORALITE® 5910 High Intensity Prismatic Grade and coloured transparent laminate ORALITE® 5061 Transparent Film

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 38	Coefficient of retroreflection ETA 12/0478 tab. 39	Impact resistance ETA 12/0478 tab. 41	Resistance to weathering ETA 12/0478 tab. 42 und 43
on white sheeting	ORALITE® 5910-010 High Intensity Prismatic Grade and				
Yellow	ORALITE® 5061-020 Transparent Film and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5061-030 Transparent Film and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5061-050 Transparent Film and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5061-060 Transparent Film and ORALITE® 5090 Anti-Dew Film	pass, B2	R2 Europe	pass	pass

Original dyed retroreflective-sheeting ORALITE® 5910 High Intensity Prismatic Grade and Lettering-Film

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5081-070 Lettering Film and ORALITE® 5090 Anti-Dew Film	NR1	-	pass	pass

**Anti-Graffiti:**

The original dyed retroreflective sheeting is accepted to be laminated with the clear protective overlay film ORALITE® 5095 Anti-Graffiti Film for the following colours.

Original dyed retroreflective-sheeting ORALITE® 5910 High Intensity Prismatic Grade


Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor ETA 12/0478 tab. 26	Coefficient of retroreflection ETA 12/0478 tab. 27	Impact resistance ETA 12/0478 tab. 29	Resistance to weathering ETA 12/0478 tab. 30 und 31
White	ORALITE® 5910-010 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass
Yellow	ORALITE® 5910-020 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass
Red	ORALITE® 5910-030 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass
Blue	ORALITE® 5910-050 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass
Green	ORALITE® 5910-060 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass
Brown	ORALITE® 5910-080 High Intensity Prismatic Grade and ORALITE® 5095 Anti-Graffiti Film	pass, B2	R2 Europe	pass	pass

Original dyed retroreflective-sheeting ORALITE® 5910 High Intensity Prismatic Grade and Lettering-Film

Colour	Name of the product	Visibility characteristics		Durability	
		Daylight chromaticity & luminance factor EN 12899-1 7.3.1.3	Coefficient of retroreflection EN 12899-1 4.1.1.4	Impact resistance EN 12899-1 4.1.2.1	Resistance to weathering EN 12899-1 4.1.1.5
Black	ORALITE® 5081-070 Lettering Film and ORALITE® 5095 Anti-Graffiti Film	NR1	-	pass	pass

The manufacturer of the fixed vertical road traffic sign is responsible for conformity with the mandated characteristics according to EN 12899-1 by using these materials.

Hagen, 21 March 2014

Christian Barden  
Dipl.-Ing.  
Leiter StrAus-Zert